

# GRUJ Conduit Outlet Boxes with Multiple Hubs

## Explosionproof, Dust-Ignitionproof

UNILETS™ for use with Threaded Metal Conduit.

### NEC/CEC:

Class I, Division 1 and 2, Groups C, D  
Class II, Division 1 and 2, Groups E, F, G  
Class III

### Applications

- Complies with a wide range of classified area requirements.
- Corrosion-resistant: ideal indoors or out.
- For pulling of wires.
- Connect conduit lengths and change direction of conduit runs.
- Provide access for maintenance.

### Features

- Malleable iron bodies have high tensile strength and ductility. Provides great resistance to corrosion, impact, and shock.
- Accurately tapped, tapered hub threads for tight, rigid joints and ground continuity.
- Furnished with covers.
- General purpose wiring.
- Union hubs permit easy wiring.
- Externally threaded body with internally threaded cover.
- Smooth, rounded integral bushing in each hub type box protects conductor insulation.

### Standard Materials

- Bodies and covers: malleable iron

### Standard Finishes



- Bodies and covers: triple-coat — (1) zinc electroplate, (2) chromate, and (3) epoxy powder coat

### NEC Certifications and Compliances

- UL Standard: UL 886 (UL 1203)
- UL Listed: E10444
- CSA Standard: C22.2 No. 25, C22.2 No. 30
- CSA Certified: 013017

Appleton®

ENCLOSURES AND JUNCTION BOXES: NEC/CEC EXPLOSIONPROOF OUTLET BOXES

|   | Number and Size of Hubs |          |          |          | Capacity<br>dm <sup>3</sup> (in <sup>3</sup> ) | Catalog<br>Number |
|---|-------------------------|----------|----------|----------|--|-------------------|
|   | Each Side               | Top      | Bottom   | Back     |  |                   |
| <b>GRUJ Box with Cover</b>  |                         |          |          |          |  |                   |
| <i>Externally threaded malleable iron body complete with internally threaded malleable iron surface cover; choice of hub arrangements, furnished with close-up plugs for all but three 3/4" hubs. Cover opening — 82.6 mm (3.25")</i> |                         |          |          |          |  |                   |
|    | 2 — 3/4"                | 2 — 3/4" | 1 — 3/4" | None     | 0.41 (25.0)                                    | <b>GRUJ-1P</b>    |
|   | 2 — 3/4"                | 2 — 3/4" | 1 — 3/4" | 4 — 3/4" | 0.41 (25.0)                                    | <b>GRUJ-2P</b>    |
|   | 2 — 3/4"                | 2 — 3/4" | 1 — 3/4" | 4 — 1"   | 0.41 (25.0)                                    | <b>GRUJ-3P</b>    |
| <b>GRU Covers</b>   |                         |          |          |          |  |                   |
| <i>Malleable iron with internal threads. Cover opening — 82.6 mm (3.25")</i>  |                         |          |          |          |  |                   |
|    | Surface                 |          |          |          |  | <b>GRUK-S</b>     |

### Dimensions in Millimeters (Inches)

